

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name BRITESIL® C24 Hydrous Sodium Silicate
Alternative names Hydrous sodium silicate powder , (1.6<MR<=2.6)
CAS No. 1344-09-8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s) General purpose industrial chemical for use in a wide range of applications.
Binding agent ; Corrosion inhibitor ; Dust binding agent ; Flame retardant or fire preventing agent ; Flotation agent ; Stabiliser ; Viscosity control agent ; Intermediate

Uses advised against None known.

1.3 Details of the supplier of the safety data sheet

Company Identification PQ Corporation
P.O. Box 840
Valley Forge
PA 19482
USA

Telephone: +1 610-651-4200
E-Mail (competent person) sds.uk@pqcorp.com

1.4 Emergency telephone number

Emergency Phone No. +1 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification H318 : Serious eye damage/irritation Category 1
H315 : Skin corrosion/irritation Category 2
H335 : STOT - single exposure Category 3

Hazards summary

Alkaline.
Risk of serious damage to eyes.
Irritating to respiratory system and skin. Can etch glass if not promptly removed.

2.2 Label elements

Hazard pictogram(s)



Signal word(s)

Danger

Hazard statement(s)

H318: Causes serious eye damage.
H315: Causes skin irritation.
H335: May cause respiratory irritation.

Precautionary statement(s)

P261: Avoid breathing dust.
 P262: Do not get in eyes, on skin, or on clothing.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3 Other hazards Not classified as PBT or vPvB.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Regulation (EC) No. 1272/2008 (CLP)

Ingredient(s)	%W/W	CAS No.	EINECS No. / REACH Registration	Hazard symbol(s) and hazard statement(s)
Silicic acid, sodium salt (1.6<MR<=2.6) Powder	82.5	1344-09-8	215-687-4	H318 : Eye Dam. 1 ; H315 : Skin Irrit. 2 ; H335 : STOT SE 3 ;
Water	17.5	7732-18-5	231-791-2	Not classified

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Eye Contact Irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 15 minutes. Obtain immediate medical attention.

Skin Contact Wash affected skin with plenty of water. If symptoms develop, obtain medical attention.

Inhalation Remove patient from exposure, keep warm and at rest. Obtain medical attention.

Ingestion Do not induce vomiting. Wash out mouth with water and give 200-300 ml (half a pint) of water to drink. Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Alkaline.
 Risk of serious damage to eyes.
 Irritating to respiratory system and skin.
 The toxicity of sodium silicate is dependent on the silica to alkali ratio and on the pH.

4.3 Indication of any immediate medical attention and special treatment needed

Obtain immediate medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing Media Compatible with all standard fire fighting techniques.

Unsuitable extinguishing Media None known.

5.2 Special hazards arising from the substance or mixture Not applicable. Inorganic powder or granules. Non-combustible.

5.3 Advice for fire-fighters None.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing. Wear eye/face protection. An approved dust mask should be worn if dust is generated during handling. See Section: 8.2

6.2 Environmental precautions

Do not allow to enter drains, sewers or watercourses. Advise Authorities if spillage has entered water course or sewer or has contaminated soil or vegetation.

6.3 Methods and materials for containment and cleaning up

Caution - spillages may be slippery. Avoid generation of dust. Sweep or preferably vacuum up and collect in suitable containers for recovery or disposal.

6.4 Reference to other sections

See Also Section 8.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Avoid generation of dust. Emergency shower and eye wash facilities should be readily available. See Also Section 8.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed and dry. Unsuitable containers: Aluminium See Also Section 10.

7.3 Specific end use(s)

See also Annex to the extended Safety Data Sheet.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

SUBSTANCE.	Occupational Exposure Limits
Silicic acid, sodium salt	No Occupational Exposure Limit assigned. An exposure limit of 2 mg/m ³ (15 min TWA) is recommended by analogy with sodium hydroxide (UK EH40).

8.2 Exposure controls

Wear protective equipment to comply with good occupational hygiene practice. Do not eat, drink or smoke at the work place.

8.2.1 Appropriate engineering controls

Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of process conditions.

8.2.2 Personal Protection
Respiratory protection

Avoid inhalation of dusts. Wear suitable respiratory protective equipment if working in confined spaces with inadequate ventilation or where there is any risk of the exposure limits being exceeded. Advice on respiratory protective equipment is given in the HSE (Health and Safety Executive) publication HS(G)53.

**Eye/face protection
Skin protection**

Dust mask: FFP2 (EN 149).
Chemical goggles (EN 166).
Wear suitable protective clothing and gloves.
Plastic or rubber gloves. For example EN374-3, level 6 breakthrough time (>480min).
Wear suitable overalls. For example EN ISO 13982 (dust), EN 14605 (liquid splashes).

8.2.3 Environmental Exposure Controls

The primary hazard of sodium silicate is the alkalinity. Avoid generation of dust. Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties
Appearance

Powder. White.

Odour	Odourless.
Odour Threshold (ppm)	Not applicable.
pH (Value)	Alkaline.
Freezing Point (°C)	Not applicable.
Melting Point (°C)	> 1000
Boiling Point (°C)	Not applicable.
Flash Point (°C) [Closed cup]	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Explosive Limit Ranges	Not applicable.
Vapour Pressure (mm Hg)	Not applicable.
Vapour Density (Air=1)	No data.
Density (g/ml)	No data.
Solubility (Water)	Soluble.
Solubility (Other)	No data.
Partition Coefficient	No data.
Auto Ignition Point (°C)	Not applicable.
Decomposition Temperature (°C)	Not applicable.
Viscosity (mPa. s)	Not applicable.
Explosive properties	Not applicable.
Oxidising Properties	Not applicable.
9.2 Other information	No data.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	See Section: 10.3
10.2 Chemical stability	Stable.
10.3 Possibility of hazardous reactions	When arc welding vessels containing aqueous solutions of this material, take care to control any explosion risk from hydrogen evolved by electrolysis. Aqueous solutions will react with aluminium, zinc, tin and their alloys evolving hydrogen gas which can form an explosive mixture with air. Can react violently if in contact with acids. Can react with sugar residues to form carbon monoxide.
10.4 Conditions to avoid	See Section: 10.3
10.5 Incompatible materials	See Section: 10.3
10.6 Hazardous decomposition product(s)	Hydrogen

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Ingestion	All symptoms of acute toxicity are due to high alkalinity. Material will cause irritation. Oral LD50 (rat) 3400 mg/kg bw
Inhalation	Dust is irritant to the respiratory tract. All symptoms of acute toxicity are due to high alkalinity. Inhalation LC50 (rat) >2.06 g/m ³
Skin Contact	Material will cause irritation. Dermal LD50 (rat) >5000 mg/kg bw
Eye Contact	Material will cause severe irritation. Risk of serious damage to eyes.

Skin corrosion/irritation

Irritating to skin.

Serious eye damage/irritation

Irritating to eyes.

Sensitisation

Not sensitising.

Mutagenicity

No evidence of genotoxicity. In vitro/in vivo negative.

Carcinogenicity

No structural alerts.

Reproductive toxicity

No evidence of reproductive toxicity or developmental toxicity.

STOT - single exposure

Irritating to respiratory system.

STOT - repeated exposure

Not classified. NOAEL oral (rat) >159 mg/kg bw/d

Aspiration hazard

Not classified

Other information

Human experience confirms that irritation occurs when sodium silicates get on clothes at the collar, cuffs or other areas where abrasion may occur.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity	Fish (Brachydanio rerio) LC50 (96 hour) 1108 mg/l Aquatic invertebrates: (Daphnia magna) EC50 (48 hour) 1700 mg/l
12.2 Persistence and degradability	Inorganic. Soluble silicates, upon dilution, rapidly depolymerise into molecular species indistinguishable from natural dissolved silica.
12.3 Bioaccumulative potential	Inorganic. The substance has no potential for bioaccumulation.
12.4 Mobility in soil	Not applicable.
12.5 Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6 Other adverse effects	The alkalinity of this material will have a local effect on ecosystems sensitive to changes in pH.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods	Discharge of this product to sewage treatment works is dependent on local regulations with regard to pH controls. Disposal should be in accordance with local, state or national legislation.
-------------------------------------	---

SECTION 14: TRANSPORT INFORMATION

14.1 UN number	Not applicable
14.2 Proper Shipping Name	Not applicable.
14.3 Transport hazard class(es)	Not applicable.
14.4 Packing group	Not applicable.
14.5 Environmental hazards	Not classified as a Marine Pollutant.
14.6 Special precautions for user	No special packaging requirements. Unsuitable containers: Aluminium
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

SECTION 15: REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

TSCA Inventory Status: Reported/Included.

AICS Inventory Status: Reported/Included.

DSL/NDSL Inventory Status: Reported/Included.

CERCLA: No CERCLA Reportable Quantity has been established for this material.

SARA TITLE III: Not an Extremely Hazardous Substance under §302.

Not a Toxic Chemical under §313.

Hazard Categories under §§311/312: Acute 3,0,0

15.2 Chemical Safety Assessment


A Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Data referenced in this eSDS is from company-owned information and from data legitimately accessed by PQ Corporation through membership of Industry Consortia or other agreements. This includes data relating to toxicology, ecotoxicology, DNELs, PNECs and other information in this eSDS and its annex.

This SDS was last reviewed: 02/2015

The following sections contain revisions or new statements: No significant changes required to this version at last review.

GHS Classification	H318 : Serious eye damage/irritation Category 1 H315 : Skin corrosion/irritation Category 2 H335 : STOT - single exposure Category 3
Signal word(s)	Danger
Hazard pictogram(s)	
Hazard statement(s)	H318: Causes serious eye damage. H315: Causes skin irritation. H335: May cause respiratory irritation.
Precautionary statement(s)	P261: Avoid breathing dust. P262: Do not get in eyes, on skin, or on clothing. P280: Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

GLOSSARY

H318: Causes serious eye damage.

H315: Causes skin irritation.

H335: May cause respiratory irritation.

STOT SE 3 : Specific target organ toxicity — single exposure Category 3

R41: Risk of serious damage to eyes.

R37/38: Irritating to respiratory system and skin.

DNEL : Derived No Effect Level

PNEC : Predicted No Effect Concentration

PBT: Persistent, Bioaccumulative and Toxic

EC Classification : According to Directive 67/548/EEC & Directive 1999/45/EC

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. PQ Corporation gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. PQ Corporation accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.