

Trade Name: **BRITESIL® C20 Hydrous Sodium Silicate**
Date Prepared: **January 4, 2010** Page: 1 of 5

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: **BRITESIL® C20 Hydrous Sodium silicate**
Product description: **A 2.0 weight ratio hydrous sodium silicate powder**
Product Use: **Detergents**
Manufacturer: **PQ Corporation**
P. O. Box 840, Valley Forge, PA USA
Phone number: 610-651-4200
Supplier: **National Silicates**
429 Kipling Ave, Etobicoke, ON M8Z 5C7
Phone number: 416-255-7771
Fax number: 416-201-4347
In case of emergency call: **1 416-255-7771**

2. COMPOSITION/INFORMATION ON INGREDIENTS

<i>Chemical and Common Name</i>	<i>CAS Registry Number</i>	<i>Wt. %</i>	<i>OSHA PEL</i>	<i>ACGIH TLV</i>
Silicic acid, Sodium salt;	1344-09-8	~83%	Not Established	Not Established
Sodium silicate				
Water	7732-18-5	~17%	Not Established	Not Established

3. HAZARDS IDENTIFICATION

Emergency Overview: **White, odorless, powder. Causes burns to skin and eyes. Dust irritating to respiratory tract. Due to high pH of product, release into surface water is harmful to aquatic life. Noncombustible. Reacts with acids and some organics.**

Eye contact: **Causes eye burns.**

Skin contact: **Causes skin burns.**

Inhalation: **Dust irritating to respiratory tract.**

Ingestion: **Causes burns to digestive tract..**

Chronic hazards: **No known chronic hazards. Not listed by NTP, IARC or OSHA as a carcinogen.**

Physical hazards: **Can etch glass if not promptly removed.**



Trade Name:
Date Prepared:

BRITESIL® C20 Hydrous Sodium Silicate

January 4, 2010

2 of 5

4. FIRST AID MEASURES

Eye: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention.

Skin: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: If swallowed, DO NOT induce vomiting. Get medical attention immediately. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Flammable limits: This material is noncombustible.

Extinguishing Media: This material is compatible with all extinguishing media

Hazards to fire-fighters: See Section 3 for information on hazards when this material is present in the area of a fire.

Fire-fighting equipment: The following protective equipment for fire fighters is recommended when this material is present in the area of a fire: chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots.

Hazardous Combustion Products: Not available

Explosion data

Sensitivity to mechanical impact and static discharge: Not applicable

6. ACCIDENTAL RELEASE MEASURES

Personal protection: Wear chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots, NIOSH-approved dust respirator where dust occurs. See section 8.

Environmental Hazards: Sinks and mixes with water. High pH of this material is harmful to aquatic life, see Section 12.

Small spill cleanup: Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust. Use appropriate Personal Protective Equipment (PPE). See section 8.

Large spill cleanup: Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material. Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust. Use appropriate Personal Protective Equipment (PPE). See section 8. In case of contact with water, prevent runoff from entering into storm sewers and ditches which lead to natural waterways. Neutralize contaminated area and flush with large quantities of water. Comply with applicable environmental regulations.

CERCLA RQ (US): There is no CERCLA Reportable Quantity for this material. If a spill goes off site, notification of state and local authorities is recommended.



Trade Name:
Date Prepared:

BRITESIL® C20 Hydrous Sodium Silicate

January 4, 2010

3 of 5

7. HANDLING AND STORAGE

Handling: Do not get in eyes. Avoid contact with skin and clothing. Avoid breathing dust. Keep container closed. Promptly clean up spills.

Storage: Keep containers closed. Store in clean steel or plastic containers. Separate from acids, reactive metals, and ammonium salts. Do not store in aluminum, fiberglass, copper, brass, zinc or galvanized containers. This product can absorb water from the air. In case of high humidity or storage for extended periods of time, use plastic bags to enclose product containers to avoid caking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls: Use only with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within direct access.

Respiratory protection: Use a NIOSH-approved dust respirator where dust occurs. Observe Provincial regulations for respirator use.

Skin protection: Wear body-covering protective clothing and gloves.

Eye protection: Wear chemical goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Powder.

Color: White.

Odor: Odorless or musty odor.

Odor threshold: Not applicable

pH: Approximately 12.4

Bulk density: Approximately 30 lbs/ft³ untamped.

Solubility in water: Soluble in all proportions.

Flash point: Not applicable

Auto-ignition temperature: Not applicable

Vapor pressure: Not applicable

Vapor density: Not applicable

Evaporation rate: Not applicable

Boiling point: Not applicable

Freezing point: Not applicable

Coefficient of water /oil distribution: Not applicable

10. STABILITY AND REACTIVITY

Stability: This material is stable under all conditions of use and storage.

Conditions to avoid: None.

Materials to avoid: Generates heat when mixed with acid. May react with ammonium salt solutions resulting in evolution of ammonia gas. Flammable hydrogen gas may be produced on contact with aluminum, tin, lead, and zinc.

Hazardous decomposition products: Hydrogen.



Trade Name:
Date Prepared:

BRITESIL® C20 Hydrous Sodium Silicate

January 4, 2010

4 of 5

11. TOXICOLOGICAL INFORMATION

<i>Acute Data:</i>	<p>When tested for primary irritation potential, similar materials were severely irritating or corrosive to the skin and eyes. Human experience indicates that irritation occurs when sodium silicates get on clothes at the collar, cuffs or other areas where contact and abrasion may occur.</p> <p>The acute oral toxicity of this product has not been tested. When sodium silicates were tested on a 100% solids basis, their single dose acute oral LD₅₀ in rats ranged from 1500 mg/kg to 3200 mg/kg. The acute oral lethality resulted from nonspecific causes. This product contains approximately 82.5% sodium silicate.</p>
<i>Subchronic Data:</i>	<p>In a study of rats fed sodium silicate in drinking water for three months, at 200, 600 and 1800 ppm, changes were reported in the blood chemistry of some animals, but no specific changes to the organs of the animals due to sodium silicate administration were observed in any of the dosage groups. Another study reported adverse effects to the kidneys of dogs fed sodium silicate in their diet at 2.4g/kg/day for 4 weeks, whereas rats fed the same dosage did not develop any treatment-related effects. Decreased numbers of births and survival to weaning was reported for rats fed sodium silicate in their drinking water at 600 and 1200 ppm.</p>
<i>Special Studies:</i>	<p>Frequent ingestion over extended periods of time of gram quantities of silicates is associated with the formation of kidney stones and other siliceous urinary calculi in humans.</p> <p>Mutagenicity: Sodium silicate was not mutagenic to the bacterium E. Coli when tested in a mutagenicity bioassay.</p> <p>Carcinogenicity: There are no known reports of carcinogenicity of sodium silicates. Sodium silicate is not listed by IARC, NTP or OSHA as a carcinogen.</p> <p>Sensitization to product: Not applicable</p> <p>Reproductive toxicity: Not applicable</p> <p>Teratogenicity: Not applicable</p> <p>Name of toxicologically synergistic products: Not applicable</p>

12. ECOLOGICAL INFORMATION

<i>Eco toxicity:</i>	<p>The following data is reported for sodium silicates on a 100% solids basis: A 96 hour median tolerance for fish (<i>Gambusia affinis</i>) of 2320 ppm; a 96 hour median tolerance for water fleas (<i>Daphnia magna</i>) of 247 ppm; a 96 hour median tolerance for snail eggs (<i>Lymnaea</i>) of 632 ppm; and a 96 hour median tolerance for Amphipoda of 160 ppm. This product contains approximately 82.5% sodium silicate.</p>
<i>Environmental Fate:</i>	<p>This material is not persistent in aquatic systems, but its high pH when undiluted or unneutralized is acutely harmful to aquatic life. Diluted material rapidly depolymerizes to yield dissolved silica in a form that is indistinguishable from natural dissolved silica. It does not contribute to BOD. This material does not bioaccumulate except in species that use silica as a structural material such as diatoms and siliceous sponges. Where abnormally low natural silica concentrations exist (less than 0.1 ppm), dissolved silica may be a limiting nutrient for diatoms and a few other aquatic algal species. However, the addition of excess dissolved silica over the limiting concentration will not stimulate the growth of diatom populations; their growth rate is independent of silica concentration once the limiting concentration is exceeded. Neither silica nor sodium will appreciably bioconcentrate up the food chain.</p>
<i>Physical/Chemical:</i>	<p>Sinks and mixes with water. Only water will evaporate from this material.</p>



Trade Name:
Date Prepared:

BRITESIL® C20 Hydrous Sodium Silicate

January 4, 2010

5 of 5

13. DISPOSAL CONSIDERATIONS

Disposal Method: Neutralize and landfill solids in accordance with federal, provincial and local regulations.

14. TRANSPORT INFORMATION

TDG UN Status: This material is not regulated hazardous material for transportation.

15. REGULATORY INFORMATION

WHMIS (Canada): Class D2B
This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* and the MSDS contains all the information required by the *Controlled Products Regulations*.

DSL (Canada): All components of this formulation are listed on the CEPA-DSL
CERCLA (US): No CERCLA Reportable Quantity has been established for this material.
SARA TITLE III (US): Not an Extremely Hazardous Substance under §302. Not a Toxic Chemical under §313. Hazard Categories under §§311/312: Acute

TSCA (US): All ingredients of this material are listed on the TSCA inventory.
FDA: The use of sodium silicate is authorized by FDA as a boiler water additive for the production of steam that will contact food pursuant to 21 CFR §173.310; as a component of zinc-silicon dioxide matrix coatings on food contact surfaces pursuant to 21 CFR §175.390(c); as a GRAS substance when migrating from cotton fabric used in dry food packaging pursuant to 21 CFR §182.70; and as a GRAS substance when migrating to food from paper and paperboard products pursuant to 21 CFR §182.90.

16. OTHER INFORMATION

Prepared by: EHS Dept
Supersedes revision of: July 14, 2006

THE INFORMATION ON THIS SAFETY DATA SHEET IS BELIEVED TO BE ACCURATE AND IT IS THE BEST INFORMATION AVAILABLE TO NATIONAL SILICATES THIS DOCUMENT IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONS FOR HANDLING A CHEMICAL BY A PERSON TRAINED IN CHEMICAL HANDLING. NATIONAL SILICATES MAKES NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED WITH RESPECT TO SUCH INFORMATION OR THE PRODUCT TO WHICH IT RELATES, AND WE ASSUME NO LIABILITY RESULTING FROM THE USE OR HANDLING OF THE PRODUCT TO WHICH THIS SAFETY DATA SHEET RELATES. USERS AND HANDLERS OF THIS PRODUCT SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION PROVIDED HEREIN FOR THEIR OWN PURPOSES.

