

**Gasil® Silicas  
For High  
Performance  
Coatings**



# Gasil® HP260

**Gasil® HP260** is part of a range of high performance silica gels specifically designed to provide outstanding matting efficiency in coil, general industrial and other surface coatings systems.

**Gasil® HP260** provides excellent matting efficiency combined with minimal effect on clarity and mechanical film properties in thin film applications.

## **Gasil® HP260 Benefits:**

- Optimal matting efficiency from ultra high pore volume and controlled particle size distribution
- Product consistency
- Ease of dispersion
- Film clarity
- Raw material cost savings

## **Average Particle Size of Gasil® HP260**

Malvern Mastersizer, microns 6.4-7.7

## **Typical Properties of GASIL® HP260**

Pore volume, (ml/g)	1.8
Loss at 1000° C (%)	3
pH (5% aqueous)	3.5



P.O. Box 840, Valley Forge,  
Pennsylvania 19482-0840 USA  
Tel.: 01-800-944-7411

[www.pqcorp.com](http://www.pqcorp.com)

## **Gasil® HP260 Storage & Handling:**

Store the product in unopened bags in a dry place with temperatures between 35° F and 95° F. Handle sensibly to minimize creation of dust and build up of static electricity. Product is amorphous (no crystalline silica). Please consult the MSDS available on request.

## **Packaging:**

Gasil® HP260 is available in 30 pound or 12.5 kilogram bags.

The information presented herein is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Since the conditions of use are beyond our control we disclaim any liability, including for patent infringement, incurred in connection with the use of these products, data or suggestion. Copyright PQ Corporation