



Gasil® IJ24

Gasil® IJ24 is a general purpose silica gel designed as an effective matting agent for coil, general industrial and other surface coatings.

Gasil® IJ24 provides excellent matting combined with minimal effect on viscosity.

Gasil® IJ24 Benefits:

- Optimal matting efficiency from a controlled particle size distribution
- Product consistency
- Ease of dispersion
- Film clarity
- Raw material cost savings

Gasil® IJ24 Storage & Handling:

Store the product in unopened bags in a dry place with temperatures between 35° F and 95° F. Handle sensibly to minimize creation of dust and build up of static electricity. Product is amorphous (no crystalline silica). Please consult the MSDS available on request.

Packaging:

Gasil® IJ24 is available in 44 pound bags and 20 kilogram bags.

The information presented herein is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Since the conditions of use are beyond our control we disclaim any liability, including for patent infringement, incurred in connection with the use of these products, data or suggestion. Copyright PQ Corporation

Average Particle Size of Gasil® IJ24

Malvern Mastersizer, microns 6.0 – 7.7

Typical Properties of GASIL® IJ24

Pore volume, (ml/g)	1.2
Loss at 1000° C (%)	5
pH (5% aqueous)	6



P.O. Box 840, Valley Forge,
Pennsylvania 19482-0840 USA
Tel.: 01-800-944-7411

www.pqcorp.com