



Typical Property Data for PQ® Sorbsil R92F

PQ's Sorbsil® silicas are synthetic amorphous silica dioxide (SiO₂) - mixture silica hydrogels. Sorbsil® R92F contains citric acid and is used as a non-dusty, refining product for edible oils and the removal of impurities. Our silicas should be stored in unopened bags away from strong odors, in a dry place. Ideally temperatures should remain between 35°F/2°C and 95°F/35°C. It should be handled sensibly to minimize creation of dust and build-up of static electricity. Sorbsil R92F is typically supplied in bulk trucks or 1000 pound sacks, 2 sacks per pallet.

Our Sorbsil® products are FDA approved for various applications as a direct additive for food at levels up to 2% and/or as defined by the applicable sections of Title 21 Code of Federal Regulations Part 172.480 for silicon dioxide.

PQ Sorbsil® R92F is characterized by the property data shown below. The properties are typical values, along with manufacturing specifications. Physical properties are measured at room temperature, approximately 20°C (68°F). For more information, please contact PQ Technical Service at 416-201-4355.

PQ CORPORATION

CORPORATE HEADQUARTERS

PO Box 840
Valley Forge, PA 19482-0840
Phone: 800-944-7411

IN NORTH AMERICA

Joliet, IL 60435
USA
T: +1 815 727 3651

IN SOUTH AMERICA

Rua Cenzo Sbrighi 27
1° andar cj 12 - Água Branca
5036-011 - São Paulo
SP Brazil
T: +55 (0)11 3613 9900

IN AFRICA

169 Tedstone Road
PO Box 14016
Wadeville 1422, Gauteng
South Africa
T: +27 (0)11 820 7111

IN EUROPE

Warrington
England
WA5 1AB
T: +44 (0)1925 416100

IN ASIA/PACIFIC RIM

435 Orchard Road
#19-05 Wisma Atria
Singapore 238877
T: +65 6838 7290

PQ Corporation is a leading producer of silicate, silicas, zeolite, and other performance materials serving the detergent, pulp and paper, chemical, coatings, petroleum, catalyst, water treatment, construction, and beverage markets. It is a global enterprise, operating in 21 countries on five continents, and along with its chemical businesses, includes Potters Industries, a wholly owned subsidiary, which is a leading producer of engineered glass materials serving the highway safety, polymer additive, metal finishing, and conductive particle markets.

Sorbsil® R92F Properties	Typical Data	Specifications
Loss at 1000 C, %	59.1	56.0 - 66.0
Silicon Dioxide, %	40.6	34.0 - 44.0
pH (25% solution)	2.2	1.5 - 3.0
Average Particle Size, microns	18.2	14.0 - 22.0
Carbon Content, % by weight	1.3	Minimum of 1.0

Although the information and suggestions in this brochure ("information") are believed to be correct, PQ Corporation makes no representations or warranties as to the completeness or accuracy of the information. The information is supplied upon the following conditions: The persons receiving the information will determine its suitability for their purposes; PQ Corporation will not be responsible for damages of any nature whatsoever resulting from the use, or reliance upon, the information of materials, devices or products to which the information refers; No information is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any patent; PQ Corporation makes no representation or warranty, express or implied, that the use thereof will not infringe any patent; and NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE MATERIALS, DEVICES OR PRODUCTS TO WHICH THE INFORMATION REFERS.

Issue 4, July 2009

